

STRICTLY RESTRICTED**FOR COMPANY USE ONLY RESTRICTED**

The information given in this report is not to be communicated either directly or indirectly to the press or to any person not holding an official position in the CIL /GOVERNMENT.

**ENVIRONMENTAL MONITORING REPORT
OF
BHARAT COKING COAL LIMITED,
CLUSTER – XII**

(FOR THE MONTH JULY, 2024)

E. C. no. J-11015/184/2012-IA.II (M) dated 10.12.2014.



CMPDI

ISO 9001 Company
Regional Institute-II
Dhanbad, Jharkhand

CONTENTS

SL. NO.	CHAPTER	PARTICULARS	PAGE NO.
1.	CHAPTER - I	EXECUTIVE SUMMARY	3-5
2.	CHAPTER-II	INTRODUCTION	6
3.	CHAPTER-III	RESULTS	7-18
4.	CHAPTER-IV	STANDARDS AND PLANS	19-20

EXECUTIVE SUMMARY

1.0 Introduction

The purpose of environmental monitoring is to assess the quality of various attributes that affects the fauna and flora. In accordance with the quality of these attributes appropriate strategy is to be developed to control the pollution level within the permissible limits. The three major attributes are air, water and noise level.

Bharat Coking Coal Limited (BCCL), a Subsidiary company of Coal India Limited is operating Underground and Opencast Mines in Jharia Coalfield (JCF) is a part of Gondwana Coalfields located in Dhanbad district of Jharkhand, the JCF is bounded by 23°37' N to 23°52' N latitudes and 86°09' E to 86°30' E longitude occupying an area of 450 Sq.km. BCCL has awarded Environmental monitoring work of Jharia Coalfield (JCF) to Central Mine Planning & Design Institute Limited (CMPDIL). The environmental monitoring has been carried out as per the conditions laid down by the MoEF&CC while granting environmental clearance of project, consent letter issued by the respective SPCB, and other statutory requirements.

2.0 Sampling location and rationale

2.1 Ambient air sampling locations

The ambient air quality monitoring stations were selected to represent core, buffer zone area. The rationale has been based on the guidelines stipulated by MoEF&CC, consent letter of SPCB, as well as other statutory requirements.

2.2 Water sampling stations

The Water sampling stations were selected for mine sump water.

2.3 Noise level monitoring locations

Noise levels vary depending on the various activities in mining areas. The monitoring of noise level in different locations will be helpful to take appropriate mitigating measures. The rationale has been based on the guidelines stipulated by MoEF&CC, consent letter of SPCB, as well as other statutory requirements.

3.0 Methodology of sampling and analysis

3.1 Ambient air quality

Parameters chosen for assessment of ambient air quality were Particulate Matter (PM₁₀), Fine Particulate Matter (PM_{2.5}), Sulphur Di-oxide (SO₂)

and Nitrogen Oxides (NO_x). Respirable Dust Samplers (RDS) and Fine Dust Sampler (PM_{2.5} sampler) were used for sampling of PM₁₀, SO₂, & NO_x and Fine Dust Sampler (PM_{2.5} sampler) were used for sampling of PM_{2.5} at 24 hours interval once in a fortnight and the same for the gaseous pollutants. The samples were analysed in Environmental Laboratory of CMPDI, RI-II, Dhanbad.

3.2 Water quality

Water samples were collected as per standard practice. The Mine effluent samples were collected and analyzed for four parameters on fortnightly basis. Thereafter the samples were preserved and analyzed at the Environmental Laboratory of CMPDI, RI- II, Dhanbad.

3.3 Noise level monitoring

Noise level measurements in form of 'LEQ' were taken using Integrated Data Logging Sound Level Meter. Noise levels were measured in Decibels, 'A' weighted average, i.e. dB(A).

4.0 Results and interpretations

4.1 Air quality

It has been seen from the analysis results that the 24 hours average concentration parameters like PM₁₀, PM_{2.5}, SO₂ and NO_x are mostly within the permissible limits in all sampling locations as per MoEF&CC Gazette Notification No. GSR 742(E) dt 25.09.2000 Standards for Coal Mines and National Ambient Air Quality Standard -2009. Sometimes the concentration of PM₁₀ & PM_{2.5} exceeds the limits due to heavy public traffic, poor road condition, coke oven plants, burning of coal by surrounding habitants, brick making, municipal waste dumps and industries like Steel Plant, thermal Plants including their fly ash etc.

The following preventive and suppressive mitigative measures can be undertaken to contain the pollution level within prescribed level:-

- Wet drilling and controlled blasting should be practice.
- Explosive used should be optimised to restrict the dust generation.
- Transportation roads should be permanently asphalted free of ruts, potholes etc.
- Water should be sprayed on coal transportation road, service road more frequently and at regular interval.
- Dust from roads should be removed physically or mechanically.
- Greenbelts around industrial sites, service building area besides Avenue plantation along roads should be created.
- Coal dust should be suppressed by using fixed sprinklers.
- Regular maintenance of plant and machinery should be undertaken.

4.2 Water quality

The test results indicate that the major parameters compared with MoEF&CC Gazette Notification No. GSR 742(E) dt 25.09.2000

4.3 Noise Level

During the noise level survey it has been observed that the noise level in the sampling locations is within the permissible limits prescribed as per MoEF&CC Gazette Notification No. GSR 742(E) dt 25.09.2000 Standards for Coal Mines for Industrial Area and Noise pollution (Regulation and Control) Rules, 2000.

INTRODUCTION

1.0 Any industry and development activities including coal mining is bound to affect environmental attributes. There are positive as well as negative impacts of such operations. For controlling the adverse impacts a regular monitoring is essential. The environmental monitoring is being done as per the guide-lines stipulated by Ministry of Environment, Forest and Climate Change (MoEF&CC), Govt. of India.

The very purpose of environmental monitoring is to assess the quality of various attributes which affects the environment. As per quality of these attributes appropriate strategy is to be developed to control the pollution level within the permissible limits. The three major attributes are air, water and noise level.

Bharat Coking Coal has awarded Environmental Monitoring work of all Projects, Cluster wise, to Central Mine Planning & Design Institute Limited (CMPDIL). The environmental monitoring has been carried out as per conditions laid down by MoEF&CC while granting environmental clearance to different projects. CMPDI has trained manpower and well equipped laboratory to carry out monitoring, analysis and R&D work in the field of environment.

1.1 The Cluster XII is in the Central part of the Jharia coalfield. It includes Kapuria UG Mine. The cluster – XII is situated about 30 - 35 kms from Dhanbad Railway Station. The mines of this cluster - XII are operating since pre nationalization period (prior to 1972-73). It is connected by both Railway and Road. The drainage of the area is governed by Katri River.

1.2 The cluster XII is designed to produce 2.4 Mtpa (normative) and 3.12 Mtpa peak capacity of coal. The average grade of coal W-II to W-IV.

The Project has Environmental Clearance from Ministry of Environment, Forests and Climate Change (MoEF&CC) for a rated capacity of 2.4 MTPA (normative) and 3.12 MTPA peak capacity of coal production vide letter no E.C. no. J-11015/184/2012-IA.II (M) dated 10.12.2014.

Ministry of Environment, Forest and Climate Change while granting environmental clearance has given one of the General conditions that “ Four ambient air quality monitoring stations should be established in the core zone as well as in the buffer zone for PM₁₀, PM_{2.5}, SO₂, NO_x monitoring. Location of the stations should be decided based on the meteorological data, topographical features and environmentally and ecologically sensitive targets, other conditions regarding water / effluent and noise level monitoring in consultation with the State Pollution Control Board.”

In compliance of these conditions the Environmental Monitoring has been carried out & report prepared for submission to MoEF&CC & JSPCB and other statutory authorities.

AMBIENT AIR QUALITY MONITORING

2.1 Location of sampling station and their rationale:

(As per G.S.R. 742 (E) dt. 25th December, 2000)

2.1.1 Ambient Air Quality Sampling Locations

I. CORE ZONE Monitoring Location

i) Rudhi basti (A18): Industrial Area

The location of the sampling station is 23° 45' 26.60" N & 86° 18' 39.90" E. The samplers were placed at a height of approx. 1.5m above ground level at Rudhi basti.

II. BUFFER ZONE Monitoring Location

i) Block IV (A6) : Industrial area

The location of the sampling station is 23° 47' 54.00" N & 86° 16' 20.00" E The samplers were placed at a height of approx. 1.5m above ground level at Safety Office.

ii) Moonidih UGP (A17) : Industrial area

The location of the sampling station is 23° 44' 30.00" N & 86° 20' 56.00" E. The samplers were placed at a height of approx. 1.5m above ground level at project office.

iii) Murlidih 20/21 Pit(A19): Industrial Area

The location of the sampling station is 23° 43' 51.82" N & 86° 16' 21.87" E. The samplers were placed at a height of approx. 1.5m above ground level at project office.

AMBIENT AIR QUALITY DATA



CENTRAL MINE PLANNING AND DESIGN INSTITUTE LIMITED
Environment Laboratory, Regional Institute-II
Ambient Air Quality Test Report

CMPDIL, RI-II
KOYLA BHAWAN COMPLEX
DHANBAD. -826005
Phone:0326-223-850
email: rdri2cmpdi@coalindia.in

Test Report for Ambient Air Samples

Month & Year		07/2024	Cluster	Cluster XII				ULR No.	TC1012224000001053F
Customer		Environment Department, Bharat Coking Coal Limited (BCCL), Koyla Bhawan, Dhanbad (E-mail: gmenv.bccl@coalindia.in)						Date of Issue	23.09.2024
Project		Rudhi Basti		Sample Ref. No.	REM/BCCL/2024/07	Sampling Method		CMPDI/RI-II/LPM 13 , (IS 5182)	
Date of Sampling		05.07.2024		22.07.2024	Period of Analysis	05.07.2024	20.09.2024	Zone of Station:	Core Zone
Sl. No.	Parameter	Method of Analysis	Observed Values (in µg/m³)		Range Of Testing	LDL	MoEF Standards Notification dated 25th September,2000 (GSR 742 E)	NAAQS, 2009	
			1st FN	2nd FN					
1	PM ₁₀	IS -5182(Part 23):2006, R-2017	85	81	90	92	90	92	
2	PM _{2.5}	IS -5182(Part 24):2019	41	39	37	45	37	45	
3	SO ₂	IS-5182(Part-2): 2001 , R-2017	11	10	<10	<10	<10	<10	
4	NO ₂	IS-5182 (Part-6): 2006 , R-2017	20	22	21	22	21	22	

* LDL indicates Lower Detection Limit,

**All units are in $\mu\text{g}/\text{m}^3$, 24 hourly Average,

(Signature)

ANALYSED BY

(Signature)

(Gaurav Kant)

REVIEWED BY

(Signature)

(Amit Raj Mishra)

Authorised Signatory

Note: The results above relate to the samples tested as received. This report cannot be reproduced in part or full without the written permission of the HOD(Env) , CMPDI, RI-II.

---- End of Report ----

Page -1 of 1



CENTRAL MINE PLANNING AND DESIGN INSTITUTE LIMITED
Environment Laboratory, Regional Institute-II
Ambient Air Quality Test Report

CMPDIL, RI-II
 KOYLA BHAWAN COMPLEX
 DHANBAD. -826005
 Phone:0326-223-850
 email: rdri2cmpdi@coalindia.in

Test Report for Ambient Air Samples

Month & Year		07/2024	Cluster	Cluster XII			ULR No.	TC1012224000001053F	
Customer		Environment Department, Bharat Coking Coal Limited (BCCL), Koyla Bhawan, Dhanbad (E-mail: gmenv.bccl@coalindia.in)					Date of Issue	23.09.2024	
Project		Block IV		Sample Ref. No.	REM/BCCL/2024/07	Sampling Method	CMPDI/RI-II/LPM 13 , (IS 5182)		
Date of Sampling		02.07.2024		17.07.2024	Period of Analysis	02.07.2024	20.09.2024	Zone of Station:	Buffer Zone
Sl. No.	Parameter	Method of Analysis	Observed Values (in $\mu\text{g}/\text{m}^3$)		Range Of Testing	LDL	MoEF Standards Notification dated 25th September,2000 (GSR 742 E)	NAAQS, 2009	
			1st FN	2nd FN					
1	PM ₁₀	IS-5182(Part 23):2006, R-2017	95	84	10 $\mu\text{g}/\text{m}^3$ - 1000 $\mu\text{g}/\text{m}^3$	10 $\mu\text{g}/\text{m}^3$	300	100	
2	PM _{2.5}	IS-5182(Part 24):2019	51	49	10 $\mu\text{g}/\text{m}^3$ - 400 $\mu\text{g}/\text{m}^3$	10 $\mu\text{g}/\text{m}^3$	Not Specified	60	
3	SO ₂	IS-5182(Part-2): 2001 , R-2017	10	<10	10 $\mu\text{g}/\text{m}^3$ - 1050 $\mu\text{g}/\text{m}^3$	10 $\mu\text{g}/\text{m}^3$	120	80	
4	NO ₂	IS-5182 (Part-6): 2006 , R-2017	24	27	06 $\mu\text{g}/\text{m}^3$ - 420 $\mu\text{g}/\text{m}^3$	06 $\mu\text{g}/\text{m}^3$	120	80	

* LDL indicates Lower Detection Limit,

**All units are in $\mu\text{g}/\text{m}^3$, 24 hourly Average,

(Signature)

ANALYSED BY

(Signature)

(Gaurav Kant)

REVIEWED BY

(Signature)

(Amit Raj Mishra)

Authorised Signatory

Note: The results above relate to the samples tested as received. This report can not be reproduced in part or full without the written permission of the HOD(Env) , CMPDI, RI-II.

---- End of Report ----

Page -1 of 1

CENTRAL MINE PLANNING AND DESIGN INSTITUTE LIMITED
Environment Laboratory, Regional Institute-II
Ambient Air Quality Test Report



CMPDI, RI-II
 KOYLA BHAWAN COMPLEX
 DHANBAD. -826005
 Phone:0326-223-850
 email: rdri2cmpdi@coalindia.in

Test Report for Ambient Air Samples

Month & Year		07/2024	Cluster	Cluster XII			ULR No.	TC1012224000001053F	
Customer		Environment Department, Bharat Coking Coal Limited (BCCL), Koyla Bhawan, Dhanbad (E-mail: gmenv.bccl@coalindia.in)					Date of Issue	23.09.2024	
Project		Moonidih UGP		Sample Ref. No.	REM/BCCL/2024/07	Sampling Method	CMPDI/RI-II/LPM 13 , (IS 5182)		
Date of Sampling		12.07.2024		23.07.2024	Period of Analysis	12.07.2024	20.09.2024	Zone of Station:	Buffer Zone
Sl. No.	Parameter	Method of Analysis	Observed Values (in µg/m³)		Range Of Testing	LDL	MoEF Standards Notification dated 25th September,2000 (GSR 742 E)	NAAQS, 2009	
			1st FN	2nd FN					
1	PM ₁₀	IS-5182(Part 23):2006, R-2017	90	93	10 µg/m³ - 1000 µg/m³	10 µg/m³	300	100	
2	PM _{2.5}	IS-5182(Part 24):2019	48	42	10 µg/m³ - 400 µg/m³	10 µg/m³	Not Specified	60	
3	SO ₂	IS-5182(Part-2): 2001 , R-2017	<10	<10	10 µg/m³ - 1050 µg/m³	10 µg/m³	120	80	
4	NO ₂	IS-5182 (Part-6): 2006 , R-2017	24	30	06 µg/m³ - 420 µg/m³	06 µg/m³	120	80	

* LDL indicates Lower Detection Limit,

**All units are in $\mu\text{g}/\text{m}^3$, 24 hourly Average,

[Signature]

ANALYSED BY

[Signature]

(Gaurav Kant)
REVIEWED BY

[Signature]

(Amit Raj Mishra)
Authorised Signatory

Note: The results above relate to the samples tested as received. This report can not be reproduced in part or full without the written permission of the HOD(Env) , CMPDI, RI-II.

---- End of Report ----

Page -1 of 1



CENTRAL MINE PLANNING AND DESIGN INSTITUTE LIMITED
Environment Laboratory, Regional Institute-II
Ambient Air Quality Test Report

CMPDIL, RI-II
KOYLA BHAWAN COMPLEX
DHANBAD. -826005
Phone:0326-223-850
email: rdri2cmpdi@coalindia.in

Test Report for Ambient Air Samples

Month & Year		07/2024	Cluster	Cluster XII			ULR No.	TC1012224000001053F
Customer		Environment Department, Bharat Coking Coal Limited (BCCL), Koyla Bhawan, Dhanbad (E-mail: gmenv.bccl@coalindia.in)					Date of Issue	23.09.2024
Project		Murlidih 20/21 Pit	Sample Ref. No.	REM/BCCL/2024/07	Sampling Method		CMPDI/RI-II/LPM 13 , (IS 5182)	
Date of Sampling		05.07.2024	22.07.2024	Period of Analysis	05.07.2024	20.09.2024	Zone of Station:	Buffer Zone
Sl. No.	Parameter	Method of Analysis	Observed Values (in µg/m³)		Range Of Testing	LDL	MoEF Standards Notification dated 25th September,2000 (GSR 742 E)	NAAQS, 2009
			1st FN	2nd FN				
1	PM ₁₀	IS -5182(Part 23):2006, R-2017	88	110	10 µg/m³ - 1000 µg/m³	10 µg/m³	300	100
2	PM _{2.5}	IS -5182(Part 24):2019	36	67	10 µg/m³ - 400 µg/m³	10 µg/m³	Not Specified	60
3	SO ₂	IS-5182(Part-2): 2001 , R-2017	<10	<10	10 µg/m³ - 1050 µg/m³	10 µg/m³	120	80
4	NO ₂	IS-5182 (Part-6): 2006 , R-2017	23	21	06 µg/m³ - 420 µg/m³	06 µg/m³	120	80

* LDL indicates Lower Detection Limit,

**All units are in $\mu\text{g}/\text{m}^3$, 24 hourly Average,

[Signature]

ANALYSED BY

[Signature]

(Gaurav Kant)

REVIEWED BY

[Signature]

(Amit Raj Mishra)


Authorised Signatory

Note: The results above relate to the samples tested as received. This report can not be reproduced in part or full without the written permission of the HOD(Env) , CMPDI, RI-II.


---- End of Report ----

Page -1 of 1


AMBIENT AIR QUALITY AT RUDHI BASTI




AMBIENT AIR QUALITY AT BLOCK IV



AMBIENT AIR QUALITY AT MOONIDIH UGP



AMBIENT AIR QUALITY AT MURLIDIH 20/21 PIT



NOISE LEVEL QUALITY MONITORING

4.1 Location of sampling sites

- i) **Rudhi basti (N18)**
- ii) **Block IV(N6)**
- iii) **Moonidih UGP(N17)**
- iv) **Murlidih 20/21 (N19)**

4.2 Methodology of sampling and analysis

Noise level measurements in form of ' L_{EQ} ' were taken using Integrated Data Logging Sound Level Meter during day time & night time. Noise levels were measured for the complete day & night time, the Intergration time taken was one hour or 3600 seconds. Noise levels were measured in Decibels, 'A' weighted average, i.e. dB (A).

4.3 Results & Interpretations

Ambient noise levels were recorded during day time & night time and the observed values were compared with standards prescribed by MoEF&CC. The results of Noise levels recorded during day & night time on fortnightly basis are presented in tabular form along with the applicable standard permissible limits. The observed values in terms of L_{EQ} are presented. The observed values at all the monitoring locations are found to be within permissible limits.




CENTRAL MINE PLANNING AND DESIGN INSTITUTE LIMITED
Environment Laboratory, Regional Institute-II
Ambient Noise Level Test Report

CMPDIL, RI-II
 KOYLA BHAWAN COMPLEX
 DHANBAD. -826005
 Phone:0326-223-850
 email: rdri2cmpdi@coalindia.in

Month & Year	07/2024	Cluster	Cluster XII					ULR No.	TC1012224000001087F
Customer	Environment Department, Bharat Coking Coal Limited (BCCL), Koyla Bhawan, Dhanbad (E-mail: gmenv.bccl@coalindia.in)							Date of Issue	23.09.2024
Project			Sample Ref. No.	REM/BCCL/2024/07			Sampling Method	CMPDI/RI-II/LPM 22	
Sampling Stations	i	Rudhi Basti		Date of Sampling		05.07.2024	22.07.2024	Zone Category of Station:	Core Zone
Sl. No.	Parameter	Hour / Time of day	Observed Values (in Leq dB(A))	Observed Values (in Leq dB(A))	Method of Analysis	Range Of Testing	LDL	NOISE POLLUTION (REGULATION AND CONTROL) RULES, 2000 Standards	
			First Fortnight	Second Fortnight				Zones	Limits in dB
1	Noise Level dB(A)Leq - Day	06:00 - 07:00	47.7	49	CPCB, Protocol for Ambient Level Noise Monitoring - 2015	35 dB-135 dB	35 dB(A)	Industrial Commercial Residential Silence	75 65 55 50
2		07:00 - 08:00	51.3	51.6					
3		08:00 - 09:00	52.5	54					
4		09:00 - 10:00	48.6	49.3					
5		10:00 - 11:00	54	54.4					
6		11:00 - 12:00	57.9	57.1					
7		12:00 - 13:00	55.7	56.1					
8		13:00 - 14:00	57.1	57.7					
9		14:00 - 15:00	59.3	58.4					
10		15:00 - 16:00	61.6	61.9					
11		16:00 - 17:00	56.7	56.5					
12		17:00 - 18:00	54.1	54.4					
13		18:00 - 19:00	47.7	49					
14		19:00 - 20:00	48.4	48.6					
15		20:00 - 21:00	45.7	46.6					
16		21:00 - 22:00	45.6	46.7					
		Leq Day	55.3	55.4					
1	Noise Level dB(A)Leq -Night	22:00-23:00	41.2	42.1	CPCB, Protocol for Ambient Level Noise Monitoring - 2015	35 dB-135 dB	35 dB(A)	Industrial Commercial Residential Silence	70 55 45 50
2		23:00- 00:00	37.1	37.8					
3		00:00- 01:00	36.7	36.7					
4		01:00-02:00	36.7	36.3					
5		02:00-03:00	36.3	36.1					
6		03:00-04:00	40.6	41.8					
7		04:00-05:00	40.7	41.7					
8		05:00-06:00	40.8	41.7					
		Leq Night	37.9	38.6					

**All noise measurements are integrated for a 01 hour period, All units in dB(A) *LDL indicates Lower Detection Limit

Sampling Assistants
ANALYSED BY


 (Gaurav Kant)
REVIEWED BY


 (Amit Raj Mishra)
Authorised Signatory


Note: The results above relate to the samples tested as received. This report can not be reproduced in part or full without the written permission of the HOD(Env) , CMPDI, RI-II.

---- End of Report ----

Page -1 of 1

 cmpdi A Mini Ratna Company CENTRAL MINE PLANNING AND DESIGN INSTITUTE LIMITED Environment Laboratory, Regional Institute-II Ambient Noise Level Test Report CMPDI, RI-II KOYLA BHAWAN COMPLEX DHANBAD. -826005 Phone:0326-223-850 email: rdri2cmpdi@coalindia.in									
Month & Year	07/2024	Cluster	Cluster XII					ULR No.	TC1012224000001087F
Customer	Environment Department, Bharat Coking Coal Limited (BCCL), Koyla Bhawan, Dhanbad (E-mail: gmenv.bccl@coalindia.in)							Date of Issue	23.09.2024
Project		Sample Ref. No.	REM/BCCL/2024/07			Sampling Method	CMPDI/RI-II/LPM 22		
Sampling Stations	i	Block IV	Date of Sampling	02.07.2024	17.07.2024	Zone Category of Station:	Buffer Zone		
Sl. No.	Parameter	Hour / Time of day	Observed Values (in Leq dB(A))	Observed Values (in Leq dB(A))	Method of Analysis	Range Of Testing	LDL	NOISE POLLUTION (REGULATION AND CONTROL) RULES, 2000 Standards	
			First Fortnight	Second Fortnight				Zones	Limits in dB
1	Noise Level dB(A)Leq - Day	06:00 - 07:00	57.1	55.7	CPCB, Protocol for Ambient Level Noise Monitoring - 2015	35 dB-135 dB	35 dB(A)	Industrial Commercial Residential Silence	75 65 55 50
2		07:00 - 08:00	58.9	56.7					
3		08:00 - 09:00	62.4	61.3					
4		09:00 - 10:00	66	65.1					
5		10:00 - 11:00	65.5	64.5					
6		11:00 - 12:00	66.9	66.3					
7		12:00 - 13:00	62.1	65.1					
8		13:00 - 14:00	66.8	67.5					
9		14:00 - 15:00	67.2	66.2					
10		15:00 - 16:00	69.3	68.4					
11		16:00 - 17:00	71	69.8					
12		17:00 - 18:00	72	71.8					
13		18:00 - 19:00	69.6	68.4					
14		19:00 - 20:00	69.2	69.5					
15		20:00 - 21:00	63.3	62.3					
16		21:00 - 22:00	56	54.4					
		Leq Day	67.2	66.7					
1	Noise Level dB(A)Leq -Night	22:00-23:00	49.4	50	CPCB, Protocol for Ambient Level Noise Monitoring - 2015	35 dB-135 dB	35 dB(A)	Industrial Commercial Residential Silence	70 55 45 50
2		23:00- 00:00	45.5	41.8					
3		00:00- 01:00	42.2	41.3					
4		01:00-02:00	37.8	38					
5		02:00-03:00	37.4	37.6					
6		03:00-04:00	42.6	43.1					
7		04:00-05:00	42.8	42.2					
8		05:00-06:00	43.1	42					
		Leq Night	40.8	40.5					

**All noise measurements are integrated for a 01 hour period, All units in dB(A) *LDL indicates Lower Detection Limit

Sampling Assistants ANALYSED BY  (Gaurav Kant)	REVIEWED BY  (Amit Raj Mishra) Authorised Signatory
--	---


Note: The results above relate to the samples tested as received. This report can not be reproduced in part or full without the written permission of the HOD(Env) , CMPDI, RI-II.

---- End of Report ----

Page -1 of 1

 cmpdi A Mini Ratna Company CENTRAL MINE PLANNING AND DESIGN INSTITUTE LIMITED Environment Laboratory, Regional Institute-II Ambient Noise Level Test Report CMPDIL, RI-II KOYLA BHAWAN COMPLEX DHANBAD. -826005 Phone:0326-223-850 email: rdri2cmpdi@coalindia.in									
Month & Year	07/2024	Cluster	Cluster XII					ULR No.	TC1012224000001087F
Customer	Environment Department, Bharat Coking Coal Limited (BCCL), Koyla Bhawan, Dhanbad (E-mail: gmenv.bccl@coalindia.in)							Date of Issue	23.09.2024
Project		Sample Ref. No.	REM/BCCL/2024/07			Sampling Method	CMPDI/RI-II/LPM 22		
Sampling Stations	i	Moonidih UGP		Date of Sampling	12.07.2024	23.07.2024	Zone Category of Station:	Buffer Zone	
Sl. No.	Parameter	Hour / Time of day	Observed Values (in Leq dB(A)) First Fortnight	Observed Values (in Leq dB(A)) Second Fortnight	Method of Analysis	Range Of Testing	LDL	NOISE POLLUTION (REGULATION AND CONTROL) RULES, 2000 Standards	
								Zones	Limits in dB
1	Noise Level dB(A)Leq - Day	06:00 - 07:00	53.7	54.4	CPCB, Protocol for Ambient Level Noise Monitoring - 2015	35 dB-135 dB	35 dB(A)	Industrial Commercial Residential Silence	75 65 55 50
2		07:00 - 08:00	49	49.9					
3		08:00 - 09:00	57.1	58.8					
4		09:00 - 10:00	55.1	52.4					
5		10:00 - 11:00	58.3	57.2					
6		11:00 - 12:00	61.8	62.7					
7		12:00 - 13:00	59.8	59.5					
8		13:00 - 14:00	61.6	59.6					
9		14:00 - 15:00	57.6	57.2					
10		15:00 - 16:00	55.7	55.1					
11		16:00 - 17:00	55.3	55.5					
12		17:00 - 18:00	54.8	55.5					
13		18:00 - 19:00	54	54.4					
14		19:00 - 20:00	54.6	54.3					
15		20:00 - 21:00	53	52.8					
16		21:00 - 22:00	52.5	52.7					
		Leq Day	57.1	57.0					
1	Noise Level dB(A)Leq - Night	22:00-23:00	44.6	44.6	CPCB, Protocol for Ambient Level Noise Monitoring - 2015	35 dB-135 dB	35 dB(A)	Industrial Commercial Residential Silence	70 55 45 50
2		23:00- 00:00	39.6	39.7					
3		00:00- 01:00	38.8	39.7					
4		01:00-02.00	38.1	38.7					
5		02.00-03.00	37.9	38					
6		03.00-04.00	42.2	42.4					
7		04.00-05.00	43.6	43.7					
8		05:00-06:00	42	42.2					
		Leq Night	39.8	40.2					

**All noise measurements are integrated for a 01 hour period, All units in dB(A) *LDL indicates Lower Detection Limit

Sampling Assistants ANALYSED BY	 (Gaurav Kant) REVIEWED BY	 (Amit Raj Mishra) Authorised Signatory
--	--	--

Note: The results above relate to the samples tested as received. This report can not be reproduced in part or full without the written permission of the HOD(Env) , CMPDI, RI-II.


---- End of Report ----

Page -1 of 1



CENTRAL MINE PLANNING AND DESIGN INSTITUTE LIMITED
Environment Laboratory, Regional Institute-II
Ambient Noise Level Test Report

CMPDIL, RI-II
 KOYLA BHAWAN COMPLEX
 DHANBAD. -826005
 Phone:0326-223-850
 email: rdri2cmpdi@coalindia.in

Month & Year	07/2024	Cluster	Cluster XII		ULR No.			TC1012224000001087F	
Customer	Environment Department, Bharat Coking Coal Limited (BCCL), Koyla Bhawan, Dhanbad (E-mail: gmenv.bccl@coalindia.in)							Date of Issue	23.09.2024
Project			Sample Ref. No.	REM/BCCL/2024/07		Sampling Method		CMPDI/RI-II/LPM 22	
Sampling Stations	i	Murlidih(20/21)		Date of Sampling	05.07.2024	22.07.2024	Zone Category of Station:		Buffer Zone
Sl. No.	Parameter	Hour / Time of day	Observed Values (in Leq dB(A))	Observed Values (in Leq dB(A))	Method of Analysis	Range Of Testing	LDL	NOISE POLLUTION (REGULATION AND CONTROL) RULES, 2000 Standards	
			First Fortnight	Second Fortnight				Zones	Limits in dB
1	Noise Level dB(A)Leq - Day	06:00 - 07:00	51.7	51.6	CPCB, Protocol for Ambient Level Noise Monitoring -2015	35 dB- 135 dB	35 dB(A)	Industrial Commercial Residential Silence	75 65 55 50
2		07:00 - 08:00	51.8	52					
3		08:00 - 09:00	54	55.1					
4		09:00 - 10:00	53.1	54.2					
5		10:00 - 11:00	56.2	56.2					
6		11:00 - 12:00	56.6	56.3					
7		12:00 - 13:00	58.3	59.4					
8		13:00 - 14:00	58.8	58.9					
9		14:00 - 15:00	59.2	59.4					
10		15:00 - 16:00	59.5	61.5					
11		16:00 - 17:00	59.2	59.7					
12		17:00 - 18:00	57.7	57.7					
13		18:00 - 19:00	54.2	55.1					
14		19:00 - 20:00	53.9	54.2					
15		20:00 - 21:00	52.7	52.7					
16		21:00 - 22:00	52.5	52.4					
		Leq Day	56.5	57.1					
1	Noise Level dB(A)Leq -Night	22:00-23:00	37.7	37.9	CPCB, Protocol for Ambient Level Noise Monitoring -2015	35 dB- 135 dB	35 dB(A)	Industrial Commercial Residential Silence	70 55 45 50
2		23:00- 00:00	33.5	34					
3		00:00- 01:00	33.3	33.7					
4		01:00-02:00	33.2	33.6					
5		02:00-03:00	33.1	33.3					
6		03:00-04:00	37.3	36.8					
7		04:00-05:00	37.5	37.3					
8		05:00-06:00	37.7	37.4					
		Leq Night	34.6	34.5					
**All noise measurements are integrated for a 01 hour period, All units in dB(A) *LDL indicates Lower Detection Limit									
Sampling Assistants ANALYSED BY			 (Gaurav Kant) REVIEWED BY			 (Amit Raj Mishra) Authorised Signatory			
Note: The results above relate to the samples tested as received. This report can not be reproduced in part or full without the written permission of the HOD(Env) , CMPDI, RI-II.									
---- End of Report ----									
Page -1 of 1									

Ambient Air Quality Standards for Jharia Coal Field
As per the Environment (Protection) Amendment Rules, 2000 notified vide notification G.S.R. 742(E), dated 25.9.2000.

Category	Pollutant	Time weighted average	Concentration in Ambient Air	Method of Measurement
1	2	3	4	5
III Coal mines located in the coal fields of • Jharia • Raniganj • Bokaro	Suspended Particulate Matter (SPM)	Annual Average * 24 hours **	500 µg/m ³ 700 µg/m ³	- High Volume Sampling (Average flow rate not less than 1.1 m ³ /min)
	Respirable Particulate Matter (size less than 10 µm) (RPM)	Annual Average * 24 hours **	250 µg/m ³ 300 µg/m ³	Respirable Particulate Matter sampling and analysis
	Sulphur Dioxide (SO ₂)	Annual Average * 24 hours **	80 µg/m ³ 120 µg/m ³	1.Improvedwest and Gaeke method 2.Ultraviolet fluorescence
	Oxide of Nitrogen as NO ₂	Annual Average * 24 hours **	80 µg/m ³ 120 µg/m ³	1. Jacob & Hochheiser Modified (Na-Arsenic) Method 2. Gas phase Chemiluminescence

Note:

* Annual Arithmetic mean for the measurements taken in a year, following the guidelines for frequency of sampling laid down in clause 2.

** 24 hourly/8 hourly values shall be met 92% of the time in a year. However, 8% of the time it may exceed but not on two consecutive days.

NATIONAL AMBIENT AIR QUALITY STANDARDS

New Delhi the 18th November 2009

In exercise of the powers conferred by Sub-section (2) (h) of section 16 of the Air (Prevention and Control of Pollution) Act, 1981 (Act No. 14 of 1981), and in supersession of the notification No(s).S.O.384(E), dated 11th April 1994 and S.O.935(E), dated 14th NOVEMBER 1998, the Central Pollution Control Board hereby notify the National Ambient Air Quality Standards with immediate effect.


Pollutant	Time Weighted Average	Concentration in Ambient Air		Methods of Measurement
		Industrial, Residential, Rural and other Areas	Ecologically Sensitive Area (Notified by Central Government)	
Sulphur Dioxide (SO₂), µg/m³	Annual * 24 Hours **	50 80	20 80	-Improved West and Gaeke Method -Ultraviolet Fluorescence
Nitrogendioxide (NO₂), µg/m³	Annual * 24 Hours **	40 80	30 80	-Jacob &Hochheiser modified (NaOH-NaAsO ₂) Method -Gas Phase Chemiluminescence
Particulate Matter (Size less than 10µm) or PM₁₀, µg/m³	Annual * 24 Hours **	60 100	60 100	-Gravimetric -TEOM -Beta attenuation
Particulate Matter (Size less than 2.5µm) or PM_{2.5}, µg/m³	Annual * 24 Hours **	40 60	40 60	-Gravimetric -TEOM -Beta attenuation
Ozone (O₃) , µg/m³	8 Hours * 1 Hour **	100 180	100 180	-UV Photometric -Chemiluminescence -Chemical Method
Lead (Pb) , µg/m³	Annual * 24 Hours **	0.50 1.0	0.50 1.0	-AAS/ICP Method after sampling on EPM 2000 or equivalent filter paper -ED-XRF using Teflon filter
Carbon Monoxide (CO), mg/m³	8 Hours ** 1 Hour **	02 04	02 04	-Non dispersive Infrared (NDIR) Spectroscopy
Ammonia (NH₃), µg/m³	Annual * 24 Hours **	100 400	100 400	-Chemiluminescence -Indophenol blue method
Benzene (C₆H₆), µg/m³	Annual *	05	05	-Gas Chromatography (GC) based continuous analyzer -Adsorption and desorption followed by GC analysis
Benzo(a)Pyrene (BaP) Particulate phase only, ng/m³	Annual *	01	01	-Solvent extraction followed byHPLC/GC analysis
Arsenic (As), ng/m³	Annual *	06	06	-AAS/ICP Method after sampling on EPM 2000 or equivalent filter paper
Nickel (Ni), ng/m³	Annual *	20	20	-AAS/ICP Method after sampling on EPM 2000 or equivalent filter paper

* Annual Arithmetic mean of minimum 104 measurements in a year at a particular site taken twice a week 24 hourly at uniform intervals.


** 24 hourly or 8 hourly or 1 hourly monitored values, as applicable, shall be complied with 98% of the time in a year. 2% of the time, they JUNE exceed the limits but not on two consecutive days of monitoring.

NOTE:Whenever and wherever monitoring results on two consecutive days of monitoring exceed the limits specified above for the respective category, it shall be considered adequate reason to institute regular or continuous monitoring and further investigations.

Location of Air & Noise Monitoring Stations in BCCL



Water Sampling Locations in BCCL



INDEX

Cluster	Surface Water (U/S, D/S)	Name of River Nala / Effluent Water	Minel Effluent	Sampling Location	Ground Water	Sampling Location
I	SW1, SW2	Damoda River	MW1	Damoda Area	GW1	Chutway Village
II	SW3, SW4	Khudra Nala	MW2	Block II OCP	GW2	Joyrampur Village
III	SW4, SW5, SW6, SW7	Khudra Nala, Bagdigi Nala	MW3	Govindpur Colliery	GW3	Jogdih Village
IV	SW8, SW11, SW9, SW10	Kan River, Kuman Jore	MW4	Chotudih	GW4	Kankane Village
V	SW12, SW13, SW15	Jarian Nala, Ekra Nala	MW5	Mudidih	GW5	Nichitpur
VI	SW14, SW15	Ekra Nala	MW6	East Bassuria UGP	GW6	Bansara Borewell
VII	SW16, SW17	Kan Jore	MW7	Doban UGP	GW7	Humidih
VIII	SW18, SW19	Kan Jore	MW8	Doban UGP	GW8	Gharudih
IX	SW19, SW20	Kan Jore	MW9	Jemagora	GW9	Lodna
X	SW21, SW22	Damodar River	MW10	Showrah North	GW10	Showrah South
XI	SW23, SW24, SW25, SW26	Jarian Nala, Damodar River	MW11	Bhagaband UGP	GW11	Bhagaband
XII	SW27, SW28	Kan River	MW12	Kapuria	GW12	Kapuria
XIII	SW29, SW30	Damodar River	MW13	Muridih (20/21)	GW13	Muridih
XIV	SW31, SW32	Damodar River	MW14	Lohapatti	GW14	Lohapatti
XV	SW33, SW34	Khudra Nala	MW15	Kharkhane UGP	GW15	Kharkhane
XVI	SW35, SW36	Khudra River	MW16	Dahabari OCP	GW16	Pallabani Village
XVII	SW37, SW38	Barakar River	MW17	Damagoria Colliery	GW17	Chaptoria

HoD (Env.)
Bharat Coking Coal Limited
(Signature)

Regional Officer, Dhanbad
Jharkhand State Pollution Control Board
(Signature)

Legend

- Sampling Locations of Surface Water (Upstream/ Downstream)
- Sampling Locations of Mine Water
- Sampling Locations of Ground/ Drinking Water

Company	BHARAT COKING COAL LIMITED
Title	WATER SAMPLING LOCATIONS
Subject	MONITORING STATIONS
CMPDI	Scale: Not to Scale